



CLUTCH APPLICATIONS

AUTOMATED TRANSMISSION CLUTCHES



430mm Clutch for Volvo/Mack ISHIFT and M-DRIVE



NEW PART# 104460-1

1650 ft/lbs | 50x46x24N Spline | 6 Spring damper Can be used on AT2412, AT2512, AT2612 & ATO2612 transmissions

NEW PART# 104461-1

1850 ft/lbs | 50x46x24N Spline | 5 Spring damper Can be used on AT2412, AT2512, AT02512, AT2612 & AT02612 transmissions

Automated Clutch Systems

The clutch systems of the UltraShift®, UltraShift® PLUS and Fuller® Advantage Series transmissions are a fundamental piece of these transmission upgrades.





DM Clutches:

- Centrifugal design relies on engine RPM for engagement.
- Provides smooth engagement.

NEW PART# 121000-1 REMAN PART# MU121000







ECA Clutches:

- Ensure performance and efficiency with new Electric Clutch Actuation and intelligent shift selection software.
- Enables better launch and shift decisions through grade sensing, weight computation and driver throttle commands.

REMAN PART# MU122002





Heavy Duty Clutch Selector

1	Self-adjusting clutches are recommended for trucks with hydraulic linkage to reduce the risk of drivetrain damage.						Best		Better		Good	
	reduce the fisk of universalli damage.					Original Equipment Specifications (Pre-damper suffix in parentheses)		Aftermarket Specifications		Remanufactured		
	Spline Dia. – No. of Splines	Flywheel Bore Opening	No. of Springs / Damper Type	Clutch Torque lb-ft (must equal or exceed engine torque)	Facing	Advantage® Self-Adjust	Easy Pedal Advantage® Manual Adjust	EverTough® Self-Adjust	EverTough Manual Adjust	Solo® Self-Adjust	Easy Pedal® Manual Adjust	
	2" 10	7*	8	1400	4				108391-81AM		108391-81MO	
					Organic						108391-82MO	
		8.5"	10	1650	4				108391-74AM	109700-74MO	108391-74MO	
		10"	9 (Mack and Volvo 11L & 13L)	1650	4	309701-51	308925-51	109701-51AM	108935-51AM			
				1760	4				108935-61AM	109700-61MO	108935-61MO	
				1850	4	309701-68	308925-68					
				1650	6	309701-91	308925-91		108935-91AM		108935-91MO	
15				1760	6			109701-92AM				
51				1850	6	309701-98	308925-98					
5.5 inch			7	1700	4	309701-82	308925-82	109701-82AM	108925-82AM	109700-82MO	108935-82MO	
2			7 / VCT Plus®	1750	4	309701-24 (-34)	308925-24 (-34)					
				1860	4	309701-23	308925-23					
				1860	6	309701-20 (-30)	308925-20 (-30)					
			7	1860	6			109701-20AM	108925-20AM	109700-20MO	108935-20MO	
				2050	6			109701-25AM	108925-25AM	109700-25MO	108935-25MO	
			7 / VCT Plus	2050	6	309701-25 (-35)	308925-25 (-35)					
	2" – 14	10"	7 / VCT Plus	2250	6	309708-32 (-42)	308937-32 (-42)					
	Spline Dia. – No. of Splines	Flywheel Bore Opening	No. of Springs – Damper Type	Clutch Torque lb-ft (must equal or exceed engine torque)	Facing		Easy Pedal Manual Adjust		EverTough Manual Adjust		Easy Pedal Manual Adjust	
ì	1.75" – 10	7"	8	1400	4		108063-59					
14	2" — 10	7*	8	950	6	N/A	108334-6	N/A			100004 01140	
inch				1000 1150	3 Organic		108034-61B 108034-82B			N/A	108034-61MO 108034-82MO	
5				1400	4		108050-59B		108050-59AM	1	108050-59MO	

Choose size of your cast two-plate heavy-duty clutch.

Determine flywheel bore opening and select number of springs.



Choose clutch torque. Rating in chart must be equal to or exceed engine torque

Narrow clutch choice based on options. All part numbers in row meet your specs.

Advantage Series 7-spring VCT Plus – Eaton's premium damper, high torque capability with

Advantage Series Pre-Dampers – effective at quieting neutral gear idle rattle (Pre-damper suffix in parentheses in the table above)

Estimated shipping weights: 15.5" = 150 lbs, 14" = 110 lbs

Please refer to the Roadranger Warranty Guide TCWY0900 for the latest warranty time and miles offering.

6 Choose from new or remanufactured.

Advantage Series

- · Strap drive intermediate plate
- Spring separator system
- Original equipment specification
- 2 year/unlimited mileage warranty • 50,000 mile lube interval

EverTough

- · Aftermarket specification • 25,000 mile lube interval
- 1 year/unlimited mileage warranty

Remanufactured

- Economy
- 1 year/unlimited mileage warranty
- · Longer service life compared to rebuilt
- Dual zerk

Eaton Clutch for Automated Transmission

Product	Part No.	Clutch Torque lb-ft (must equal or exceed engine torque)					
Heavy-duty DM Clutch	121000-1	1750					
Heavy-duty	122002-35A	1850					
ECA Clutch and LCIB	122003-42A	2250					
430mm	104460-1	1650					
Clutch for Volvo/Mack	104461-1	1850					









Be sure to replace or resurface your flywheel when your replace your clutch





Davenport 800-383-4213

Dubuque 800-747-0752 Waterloo 800-373-3035









